

## FICHA TÉCNICA COMERCIAL COMMERCIAL TECHNICAL DATA SHEET

# SILKE

Composición · Composition

**90% PA** Poliamida · Polyamide  
**10% EA** Elastano · Elastane

Peso · Weight (+/- 6%)  
Ancho · Width (+/- 2%)

**150 g/m<sup>2</sup>**  
**150 cm Plain / 145 cm Printed**

Estabilidad Dimensional  
Dimensional Stability  
(Lavado/Washing 40° C)

Ancho · Width: **Max-5%**  
Largo · Length: **Max-5%**

Elasticidades (Dinamómetro)  
Strech to Dynamometer  
**15 N (+/- 15%)**  
(Stretch values are only valid for plain colours)

Ancho · Width: **100 %**  
Largo · Length: **75 %**



**TARIFF CODE: 60041000**

### Note · Notes :

WE RECOMMEND TESTING EACH DYE BATH BEFORE ANY TREATMENT OR APPLICATION OTHER THAN CUTTING AND SEWING TO IMPROVE OUR PRODUCTS. WE RESERVE THE RIGHT TO MODIFY THESE AS AND WHEN NECESSARY. THIS QUALITY CAN PRESENT MARK OF THE LOIN AND BARS.

**Anula y sustituye las anteriores a Mayo 2024 / Cancels and replaces the previous ones of May 2024**



STANDARD  
100  
2005AN0610  
AITEK

